



## DECLARATION OF PERFORMANCE

No. **ARM 1.02**

Table 9.1	Product Name	Sound absorption $\alpha_w$	Thermal conductivity $\lambda$ (W/mK)
	Academy Diploma	0.55	0,060
	Academy Merit	0.60(H)	0,060
	Aleria	0.45	0,060
	Atlas	0.35(H)	0,060
	Bioguard Plain	0.20(L)	0,060
	Casa	0.55(H)	0,060
	Cirrus / Cirrus Image	0.55(H)	0,060
	Contrast Circles / Contrast Squares	0.55	0,060
	Cortega	0.55(H)	0,060
	Dune / Colortone Dune	0.55	0,060
	Dune dB	0.60	0,067
	Dune Max	0.65	0,060
	Dune Supreme	0.55	0,060
	Dune Supreme Unperforated	0.15(L)	0,060
	Dune Vector	0.65	0,060
	Etna	0.45	0,060
	Etna Unperforated	0.15(L)	0,060
	Feria	0.50	0,060
	Feria Unperforated	0.15(L)	0,060
	Fine Fissured / Colortone Fine Fissured	0.60(H)	0,060
	Mezzanine DL 100	0.60	0,060
	Oasis	0.15(L)	0,060
	Plain	0.20(L)	0,060
	Retail	0.15(L)	0,060
	Sahara	0.60	0,060
	Sahara dB	0.60	0,067
	Sahara Max	0.65	0,060
	Sahara Unperforated	0.10(L)	0,060
	Sahara Vector	0.65	0,060
	Savanna	0.15(L)	0,060
	Scalacoustic	0.50	0,060
	Tatra	0.55(H)	0,060
	Visual	0.50(H)	NPD