

PAROC SW glues

SW Glue (XPG 001)



PAROC SW glue (XPG 001) is a mineral adhesive mortar with very high adhesion, high stability, and water vapor permeability. The excellent product properties make SW glue (XPG 001) the optimal choice for gluing PAROC ceiling lamellas CGL 20cy. The SW glue can be used inside and outside on all mineral and almost all organic substrates.

CE

APPROVALS:	CE
APPLICATION:	Adhesive for gluing PAROC CGL 20 lamellas to cellar and garage ceilings.
PACKAGE / STORING:	Paper bag, 25 kg / Store dry

DIMENSIONS

Product code	packing	color	EAN 64380
PAROC SW glue (XPG 001)	1 bag (25 kg)	cement grey	8580475

TECHNICAL PARAMETERS

Property	value	according to
Characteristic		
Use	<ul style="list-style-type: none"> outside and inside for gluing insulating boards on mineral and organic substrates 	
Properties	<ul style="list-style-type: none"> very high adhesion high stability very high water permeability 	
Technical data		
Density, dry powder	1200 kg/m ³	
Density, hardened	1600 kg/m ³	
Water permeability	0.17*10 ⁻⁶ mm ² /s	
Thermal conductivity	0.7 W/(m*K)	
Adhesion when pasted mineral wool board (break in the insulation)	<ul style="list-style-type: none"> > 0.02 N/mm² <p>All values are average values or approximate values. As we use natural raw materials in our products, the stated values for an individual delivery may deviate slightly. However, this does not affect the suitability of the product.</p>	

